

Lopolight P/N 200-011

Masthead light 3 nm for vessels 12-20 meter. Vertical mounting

LED (Light Emitting Diode) navigation light.

Unique and precise definition of light angles.

Rugged and unbreakable: Precision machined anodised aluminium or stainless steel housing protects the LED's and electronics.

Completely waterproof and vibrationproof: Interior is fully filled and sealed with special potting resin.

Waterproof to IP 68+ (submersible).

Lifetime over 50.000 hours or 4.200 nights.

Low power consumption – 70 to 90% less than traditional navigation lights.

Full brightness with input voltages ranging from 10 to 32 Volts.

All Lopolights have been tested during production, concluding with a 24 hour burn-in test.

Easy to install, adaptor and screws included (when applicable).



Approvals

Worldwide typeapproval
Wheelmark/M.E.D. QQ-MED-15/09-01i
MCA (UK), USCG (USA)
RINA (Italy), ELE054806CS

Measurement

92,5 mm (3,64 in) - 75 mm (2,95 in) – 28,0 mm (1,1 in) – W: 310 gram (8,2 oz)

Materials

Anodised aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane.

Supply voltage

10-32 VDC

Power consumption

1,8 Watt;
Current @ 12 VDC: 0,150 A: Current @ 24 VDC: 0,08 A

Light colors

White - 225°

Light intensity

>15cd

Light visibility

3 nm

Number ofLED's

44

Suggested feed cables

12 VDC: 2 x 0,50 mm² (maximum outer diameter 7mm)
24 VDC: 2 x 0,50 mm² (maximum outer diameter 7mm)

Expected life (hours)

50.000

Ship size (max)

12-20 meters (39,4 - 65,6 feet)

Mounting

Vertical